

Matt Polyester

General Product Description

SSAB's Matt Polyester provides good color fastness and corrosion resistance.

SSAB's wrinkled Matt Polyester is a product made for tile profiles and is available in many colors.

The reverse side of the sheet is painted as standard with a two-layer grey backside coating.

SSAB's color coated products are all manufactured according to EN 10169 + A1.

Technical Properties

Technical Properties	Matt
Gloss	1- 3
Minimum inner bending radius	2 x sheet thickness
Scratch Resistance	25N
UV Radiation Resistance	R _{uv} 3
Corrosion Resistance	RC4
Stain Resistance	Satisfactory
Highest Operating Temperature	90 °C
Fire classification	A2-s1, d0
Coating thickness, nominal	30 µm
Primer thickness, nominal	7 µm
Coating structure	Wrinkled
Steel designation	S280GD, S320GD, S350GD
Zinc Coating	275 g/m ²
Min steel thickness*	0.45 mm
Steel width**	1000- 1424 mm

* If other steel thickness is required, please contact SSAB Technical Customer Support (TCS). Max steel thickness is 1.5 mm

** Max steel width depends on steel thickness. If other steel dimensions are needed, please contact SSAB Technical Customer Support (TCS)

Colors

Please find below the standard colors available. Other shades can be agreed upon separately.

Colors	Matt
RR 11- Spruce Green	x
RR 23- Dark Grey	x
RR 29- Red	x
RR 32- Dark Brown	x
RR 33- Black	x
RR 750- Tile Red	x
RR 887- Chocolate Brown	x

Standard Reverse Side Coating

Technical Properties	
Nominal Coating Thickness	12 µm
Primer	5 µm
Color	Dark grey

Contact Information

www.ssab.com/contact